

Plaster (Floor) Skilled Trade Test Mock Written Test Paper

此文件關於批盪工（盪地台）工藝測試考題。如有需要索取此文件的中文版本，請致電 2100 9232 與
工藝測試中心聯絡。

Disclaimer

No part of this material may be reproduced or transmitted in any form or any means without the written permission of the CIC. Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions.

Enquiries

Enquiries on this Material may be made to the Trade Test Centre at:

95, Yue Kwong Road
Aberdeen
Hong Kong

Tel: (852) 2100 9232
Fax: (852) 2100 9249
Email: enquiry@cic.hk
Website: www.cic.hk

© 2015 Construction Industry Council.

1. Before plastering a floor, the plasterer must
 - (a) Level the floor surface
 - (b) Work out the levelling pie (mortar convex) (泥凸)
 - (c) Work out expansion joints
 - (d) Mix up sand mortar

2. On the following day after plastering the floor, the plasterer should
 - (a) Place miscellaneous stuff on the floor
 - (b) Continue to work
 - (c) Spray water for maintenance
 - (d) Fix cracks

3. Before plastering a floor, the plasterer should first check
 - (a) Levelling
 - (b) Materials
 - (c) Tools
 - (d) Work force

4. The ratio of floor cement mortar is
 - (a) 1:2
 - (b) 1:3
 - (c) 1:5
 - (d) 1:7

5. Before plastering a floor, the plasterer must clear the concrete floor surface and spread a layer of cement. The purpose is
- (a) Facilitate the plastering work, and speed up the progress
 - (b) Mix the mud on the floor to save materials
 - (c) Strengthen the connection between plastering materials and the floor surface
 - (d) Smooth the uneven part of the concrete floor surface
6. Which of the following environments is more likely to result in heat stroke:
- (a) Places without air-conditioner
 - (b) Extremely hot and moist places
 - (c) Uncovered places
 - (d) Places without the scorching sun
7. The thickness of a metal or plastic flashing division strip (收口分格條) is mostly
- (a) 3 mm
 - (b) 8 mm
 - (c) 10 mm
 - (d) 15 mm
8. When plastering sectioned floors, how long should it take before applying cement mortars to the section next to the completed one
- (a) 24 hours
 - (b) 36 hours
 - (c) 48 hours
 - (d) 60 hours

9. The finishing procedure for a concrete floor must be completed within
- (a) 8 hours
 - (b) 12 hours
 - (c) 16 hours
 - (d) 20 hours
10. When a floor cement mortar layer is more than 40 mm thick, it must be mixed with:
- (a) Gravel below 40 mm
 - (b) Gravel below 30 mm
 - (c) Gravel below 20 mm
 - (d) Gravel below 10 mm
11. The role of expansion joints on the floor is to
- (a) Give a face-lift
 - (b) Prevent water leakage
 - (c) Stabilize the structure
 - (d) Relieve the effect of cold and hot temperature
12. When plastering a floor, the role of a wooden screed board (木壓尺) is
- (a) Measuring the floor surface
 - (b) Screed the mortars
 - (c) Roughen a surface
 - (d) Grid and section
13. The tool used for smooth finish surface is
- (a) Wooden screed board 木壓尺
 - (b) Thin iron sheet
 - (c) Plastering trowel 薄光匙
 - (d) Corner trowel 陽角匙

14. The tool used for decorative finish surface is
- (a) Wooden screed board
 - (b) Wooden float 木磨板
 - (c) Large trowel 大灰匙
 - (d) Wooden hawk 木灰板
15. General material for separating floor joints are
- (a) Angle iron
 - (b) Iron bars
 - (c) Copper sheets
 - (d) Wooden sheet
16. The role of steel stair strips on stair treads is to
- (a) Resist pressure
 - (b) Prevent slip
 - (c) Prevent explosion
 - (d) Prevent leakage
17. A plasterer normally wears
- (a) Leather shoes
 - (b) White shoes
 - (c) Waterproof safety shoes
 - (d) Rubber boots
18. When dealing with dust or dust creating jobs, a plasterer should wear appropriate
- (a) Safety shoes
 - (b) Safety belt
 - (c) Rubber gloves
 - (d) Mouth mask or breathing device

19. Green Card is valid for

- (a) One year
- (b) Two years
- (c) Three years
- (d) Four years

20. The major purpose of the Safety in Construction Site Forum is to

- (a) Comply with the law and regulations
- (b) Introduce the design of safety products
- (c) Report and discuss the work progress
- (d) Deliver safety knowledge to the workers