



CONSTRUCTION  
INDUSTRY COUNCIL  
建造業議會

# False Ceiling Installer Skilled Trade Test Mock Written Test Paper

此文件關於假天花工工藝測試考題。如有需要索取此文件的中文版本，請致電 2100 9000 與香港建造業工藝測試中心聯絡。

## **Disclaimer**

*No part of this material may be reproduced or transmitted in any form or any means without the written permission of the CIC. Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions.*

## **Enquiries**

Enquiries on this Material may be made to the Hong Kong Construction Industry Trade Testing Centre at:

95, Yue Kwong Road  
Aberdeen  
Hong Kong

Tel: (852) 2100 9000  
Fax: (852) 2100 9090  
Email: [enquiry@cic.hk](mailto:enquiry@cic.hk)  
Website: [www.cic.hk](http://www.cic.hk)

1. Normal thickness of Gypsum Board is
  - (a) 10 (mm)
  - (b) 12 (mm)
  - (c) 15 (mm)
  - (d) 18 (mm)
  
2. Plastering Corners are mostly used at
  - (a) Position of the external corner (明角) where gyp panels are connected
  - (b) Position of the hidden corner (陰角) where gyp panels are connected
  - (c) Both of the above
  - (d) Neither of the above
  
3. Which of the following screws is used for connecting gyp panel and metal frames
  - (a) Stainless steel screws
  - (b) Grub screw (自攻螺絲)
  - (c) Tapping screw(鋼牙螺絲)
  - (d) Sharp screw(尖嘴螺絲)
  
4. Hanging material used for connecting to the ceiling (gyp board ceiling) is
  - (a) Used electric wire
  - (b) Flexible iron wire(彈弓鐵線)
  - (c) Ordinary wire
  - (d) Screw hanger
  
5. Which of the following materials is used for spaces between gyp boards
  - (a) T-angle molding (企槽)
  - (b) M-shape molding (M 槽)
  - (c) C-shape molding (C 槽)
  - (d) All of the above
  
6. Material (insulation fibre) is used as
  - (a) Decorative material for ceiling installation
  - (b) Material for gyp board ceiling
  - (c) Heat and noise control
  - (d) All of the above

7. The correct procedure for restructuring frames is
- A. Cutting the wall molding (地槽)
  - B. Cutting the T-shaped molding
  - C. Using T-shaped moldings to set up grid at the appropriate position
  - D. Using screws to fix the bottom molding according to ink lines
- (a) A, B, C, D
  - (b) B, A, D, C
  - (c) A, D, B, C
  - (d) C, A, B, D
8. The longest T-shaped molding is
- (a) 3352 (11 feet)
  - (b) 3048 (10 feet)
  - (c) 2743 (9 feet)
  - (d) 2440 (8 feet)
9. The length of screws used to fix gyp panels to T-shaped molding is generally
- (a) 25 mm (1 inch)
  - (b) 32 mm (1 1/4 inches)
  - (c) 38mm (1 1/2 inches)
  - (d) 50mm (2 inches)
10. The normal length of wall molding is
- (a) 2135 (7 feet)
  - (b) 2440 (8 feet)
  - (c) 2743 (9 feet)
  - (d) 3048 (10 feet)
11. At the construction site, guard rails (圍欄) should be installed wherever people may fall off.  
The height of such rails shall not be less than:
- (A) 300 mm
  - (B) 600 mm
  - (C) 900 mm
  - (D) 1150 mm

12. Which of the following environments is more likely to result in heat stroke:
- (a) Air-conditioned places
  - (b) Extremely hot and moist environment
  - (c) Uncovered environment in the rain
  - (d) Sitting room
13. The role of safety shoes is to
- (a) Increase walking speed
  - (b) Prevent skin disease
  - (c) Protect feet
  - (d) Improve the appearance
14. Which of the following is the right way for lifting and moving heavy loads:
- (a) Take proper position and try to keep the back straight up
  - (b) Carry more stuff each time in order to finish the work sooner
  - (c) Try to throw things to a high place for physical exercises
  - (d) Speed up the work abruptly
15. The minimum thickness of the planks for a scaffolding platform is
- (a) 20 mm
  - (b) 25 mm
  - (c) 30 mm
  - (d) 50 mm
16. Which of the following is not a facility under the Construction Sites (Safety) Regulations:
- (a) Gambling sites where it is less likely to be prosecuted
  - (b) Sufficient and suitable lighting equipment
  - (c) Sound and free escape paths
  - (d) Installing guard rails to prevent drowning
17. In case foreign particles get into your eyes, you should
- (a) Rub and press your eyes with the back of your hand
  - (b) Close your eyes tightly and ask for help
  - (c) Rinse your eyes with clean water
  - (d) Put on eye patches immediately

18. When working at height, in addition to the safety hat, you should also wear appropriately:
- (a) Safety shoes
  - (b) Warm gloves
  - (c) Eye patches
  - (d) Safety belt
19. According to the law and regulations, anyone that enters a construction site must wear
- (a) Warm gloves
  - (b) Safety belt
  - (c) Eye patches
  - (d) Safety hat
20. Working at height means the distance between the working place and the ground is
- (a) More than a meter
  - (b) More than two meters
  - (c) More than three meters
  - (d) More than four meters