

# Marble Worker (Wet Fixing) Intermediate Trade Test Study Material for Written Test

( Version : ILE-SM-EN-01 )



此文件關於雲石工（濕掛）中級工藝測試技術知識測試（筆試）內容參考資料。  
如需索取此文件的中文版本，請致電 2100 9000 與香港建造業工藝測試中心聯絡。

## Disclaimer

No part of this material may be reproduced or transmitted in any form or by any means without the written permission from the Construction Industry Council (CIC). Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions. The CIC will not assume any liability in relation to any loss or damage directly or indirectly resulted from unintended or/and unforeseeable use of this document.

This document is provided as reference for test preparation only. Under all circumstances all content in the official test papers, including but not limited to the terms and conditions therein, prevails.

The CIC reserves the right, at its sole and absolute discretion, to change, update or delete the contents in this document at any time without prior notice.

The CIC reserves all rights of final interpretation for any content in this document.

## Enquiries

Enquiries on this material may be made to Hong Kong Construction Industry Trade Testing Centre at:

Address: 95 Yue Kwong Road, Aberdeen, Hong Kong

Tel: (852) 2100 9000

Fax: (852) 2100 9090


Email: [hkcittc@cic.hk](mailto:hkcittc@cic.hk)

Website: [www.cic.hk](http://www.cic.hk)

## Marble Worker (Wet Fixing) Intermediate Trade Test Study Material for Written Test

This study material is a reference for candidate to prepare for attending written test in Intermediate Trade Test:

1. The stone corner details shown in the diagram is rabbeted corner.



2. The common thickness of a piece of marble for stone cladding is 20mm.
3. Marble is not acid resistant.
4. In stone cladding construction, fixing hold by anchor is that fixing connects marble panel to wall such as bracket and it mounted on wall by anchor bolt.
5. In stone cladding construction, fixing hold by mortar is that mortar used for holding the fixing on wall and it does not connect to the wall by anchor bolt.
6. The blending ratio of cement to sand is 1 to 3 for mortar used in grouting.
7. Datum level refers to a surface/level of reference for all levels in a construction site.
8. The common setting out technique adopted by marble workers is that reference line is set out by using line join up accurately positioned stone cladding at the beginning and end point.
9. The first step of installing marble panel onto the wall is positioning and calibrating level.
10. To lay marbles onto wall, the proper procedure is to lay it upward from the floor level to the top of the wall.
11. The general procedure of grouting (applying mortar) is grouting into joints between stone segments first.
12. The tool used to measure horizontality is spirit level.
13. Masonry shank drill bit is commonly used to drill marble.
14. According to Construction Sites (Safety) Regulations, no person should enter a construction site unless he/she is wearing a suitable safety helmet.

15. While working at height, in addition to the safety helmet, safety belt and independent lifeline should be properly used.
16. Accidents are usually caused by carelessness or negligence.
17. After finishing works in everyday, tools and work site should be cleaned.
18. In case of foreign object in the eye, clean water should be used to flush the foreign object out of the eye.
19. No person should work under a hoisted cargo in any circumstance.

#### **Precautions**

This document is provided as reference for test preparation only. Under all circumstances all content in the official test papers, including but not limited to the terms and conditions therein, prevails. There are different versions of the test paper, content include but not limited to tools, materials, equipment, drawing, construction details or procedures and different simulated site environments. Candidates should refer to the official test documents during testing.

The CIC reserves the right, at its sole and absolute discretion, to change, update or delete the contents in this document at any time without prior notice.