

Tiler (Mosaic) Intermediate Trade Test Study Material for Written Test

(Version : ITM-SM-EN-01)



此文件關於鋪瓦工（紙皮石）中級工藝測試技術知識測試（筆試）內容參考資料。
如需索取此文件的中文版本，請致電 2100 9000 與香港建造業工藝測試中心聯絡。

Disclaimer

No part of this material may be reproduced or transmitted in any form or by any means without the written permission from the Construction Industry Council (CIC). Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions. The CIC will not assume any liability in relation to any loss or damage directly or indirectly resulted from unintended or/and unforeseeable use of this document.

This document is provided as reference for test preparation only. Under all circumstances all content in the official test papers, including but not limited to the terms and conditions therein, prevails.

The CIC reserves the right, at its sole and absolute discretion, to change, update or delete the contents in this document at any time without prior notice.

The CIC reserves all rights of final interpretation for any content in this document.

Enquiries

Enquiries on this material may be made to Hong Kong Construction Industry Trade Testing Centre at:

Address: 95 Yue Kwong Road, Aberdeen, Hong Kong

Tel: (852) 2100 9000


Fax: (852) 2100 9090

Email: hkcittc@cic.hk

Website: www.cic.hk

Tiler (Mosaic) Intermediate Trade Test Study Material for Written Test

This study material is a reference for candidate to prepare for attending written test in Intermediate Trade Test:

1. The symbol shown in the diagram represents level. 
2. Surface finishes work should be start at 7 days after completed the rendering coat.
3. The function of groove/drip line is to intercept the flow of rainwater.
4. Before tiling, an ideal rendered wall surface condition is even and vertically straight.
5. During tiling with mosaic tiles on floor, the function of tile-to-tile joints is to prevent thermal expansion and contraction.
6. In general, the minimum height of dado is 600mm.
7. The function of expansion joint on floor or external walls is to relieve the effect of thermal expansion and contraction.
8. Aligned work surfaces across different walls refer to working surfaces are aligned to become a straight line.
9. Tiles laid like shoe fitting floor mirror refer to tiles laid at chamfer between wall toe and floor.
10. When laying mosaic tiles on wall, it is commonly start from bottom part of the wall.
11. To lay mosaic tiles on bottom edge of the lintel for window, the correct method is to set correct position and measure the levelness of tiles.
12. Before tiling, two reference lines with intersection angle of 90o will be marked on the floor for setting out purpose.
13. To measure verticality, plumb bob is commonly used.
14. The function of plaster's joint rule is to refine the joint between mosaic tiles.
15. According to Construction Sites (Safety) Regulations, no person should enter a construction site unless he/she is wearing a suitable safety helmet.

16. Every board or plank forming part of a working platform should be not less than 25mm in thickness.
17. After finishing works in everyday, tools and work site should be cleaned.
18. The proper attitude towards boss at work is to realize the job requirements, follow the instruction given by your supervisor and seek for advice if any queries.
19. The function of the safety shoe is to protect the feet.
20. In case of foreign object in the eye, clean water should be used to flush the foreign object out of the eye.

Precautions

This document is provided as reference for test preparation only. Under all circumstances all content in the official test papers, including but not limited to the terms and conditions therein, prevails. There are different versions of the test paper, content include but not limited to tools, materials, equipment, drawing, construction details or procedures and different simulated site environments. Candidates should refer to the official test documents during testing.

The CIC reserves the right, at its sole and absolute discretion, to change, update or delete the contents in this document at any time without prior notice.