

周大福創建集團成員 Member of CTFS Group










TOWER 1 – 3
Subsidized Sale Flat (SSF)

34-STOREY RESIDENTIAL UNITS TOTAL **2006 UNITS**

TOWER 4 [MiC ADOPTED]
Public Rental Housing (PRH)

32-STOREY RESIDENTIAL UNITS TOTAL 896 UNITS (28 UNITS EACH FLOOR)


1-Storey Basement (Carpark & Plant Rooms)






Design For Safety Examples













Tailor-made Access Platform

Safety of working at height



Heavy Lifting Frame

Safety of heavy lifting (CG Concern)



Easy-Install Safety Barrier

Safety of working at Edge







Tailor-made Access Platform



Conventional:

Access by scissor platform or long ladder to top of MiC module

May not be a proper access method and have potential risk on falling





For workers' easy and safe access to top of MiC module







Heavy Lifting Frame





Lifting points marked on MiC Module



Lifting points table shown on site

F3 F4 F5 F6 F7 F8 F9 F10 F11 F12 F13


Chain Block

Matching the lifting points on MiC module and lifting frame to ensure in stable central gravity (CG)

Need to cater 32 types of MiC modules

Ensure each lifting hook in specified lifting point


Designated lifting point for each type of module On site lifting table for reference and checking







Lifting Frame Chain-sling








Use 2m length chain-sling instead of 1.2 -1.5m length as conventional

Allow more headroom while working on MiC Prevent lifting frame hitting workers







Easy-Install Safety Barrier







Conventional barrier installation is fussy, making workers less motivation to install

Increase potential risk of falling hazard










Reduce time required on barrier installation Better protection to against falling from edge
















Cast in Tower Crane Footing





Potential risk on conventional tower crane supporting design






Tower crane support **casted in pile cap** in foundation stage

No additional supporting frame for footing required

Current approach enhance the tower crane

Stability and Safety









Mast and Jib monitoring system on metal fatigue







Metal fatigue may induced in potential tower crane incidence



Sensors installed on masts and jib sections Analysis the metal condition and create crane Al model for future crane health prediction








Crane Rope monitoring system to prevent failure





Essential to have close monitoring on tower crane rope





Wire damage presented rapid change in magnetic field

Detect rope defect by electromagnetic

Early Warning on rope replacement








DESIGN FOR SAFETY ON WORK SEQUENCES

ELS Removal Sequence

Removing ELS after completion of top slab:

High risk on **lifting** and difficult for **fire hazard** control



Strengthen the screen wall design


Allow removing 1st and 3rd layer ELS before G/F slab construction

Enhance the safety on

Lifting and Fire Hazard











DESIGN FOR SAFETY ON WORK SEQUENCES

Safety Provision on Slab Opening and Starter-bar



| 地盤男工遭鐵枝插傷肩膊 |
|-------------|
| 清醒送院搶救 |

High risk on falling from height for uncovered floor opening

| Туре | Type I (Low Risk) | Type II (High Risk) | |
|-------------------------|--|--|--|
| Opening Size | Shortest side <500mm | Shortest side ≥500mm | |
| | Cast-in metal wire mesh, grid size 100 x 100mm | | |
| Fall Arrest Measures | Cover opening by min 19mm thick plywood | U-shape starter-bar as fencing purpose | |



Easy on implementation

Minimize potential risk of falling from height in transition period









DESIGN FOR SAFETY ON WORK SEQUENCES

Fully Adoption of Metal Scaffolding



Conventional bamboo scaffolding



Special color identifying access route / staircase



Weekly checking by CP

Metal scaffolding inherently fire-resistant

Provide more secure and stable platform for workers Enhance the safety on

Fire hazard and Working at Height






DESIGN FOR SAFETY ON FAÇADE

Façades Temporary Storage Frame





KTN 24 Façades Storage Frame Plan View





Conventional façade storage frame

Façades **vertically stored** with **2 sides support**Workers easily **walk through on top**

Prevent façade Falling Hazard Easy access for workers







VR SAFETY TRAINING FOR MIC INSTALLATION



Hip Hing BIM Cave







Training to familiar with *installation*procedures and safety precaution measures










OSHC Safety Workshop



- Uplift Safety Management System
- Appoint Safety Personnels (Safety Officer and Safety Supervisor) on site
- Organise Safety Workshop and Safety Aduit
- Health and Safety Performance Incentive Scheme (HASPIS)

Pay for SSSS(4S) Scheme





CMP Room for centralized monitoring

Obtained 4S Label

CIC-4SLS 10 Main Categories of 4S products adopted in KTN project

HKHS pay for each completion item and monthly maintenance

Encourage the use of 4S on site







MIC COLLABORATION CENTER - 協3箱

Safety and Welfare Facilities











Provide safety and welfare facilities for workers

Promote and enhance the safety atmosphere





周大福創建集團成員 Member of CTFS Group

