



CONSTRUCTION
INDUSTRY COUNCIL
建造業議會

Mason Trade Test Mock Written Test Paper

此文件關於砌石工技能測試考題。如有需要索取此文件的中文版本，請致電 2100 9000 與香港建造業工藝測試中心聯絡。

Disclaimer

No part of this material may be reproduced or transmitted in any form or any means without the written permission of the CIC. Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions.

Enquiries

Enquiries on this Material may be made to the Hong Kong Construction Industry Trade Testing Centre at:

95, Yue Kwong Road
Aberdeen
Hong Kong

Tel: (852) 2100 9000

Fax: (852) 2100 9090

Email: enquiry@cic.hk

Website: www.cic.hk

© 2021 Construction Industry Council.

1. In case of foreign object in the eye, what action should take?
 - a. Use uncleaned hand to remove the foreign object out of the eye
 - b. Wear the safety goggles immediately
 - c. Close the eye and seek for help
 - d. Use clear water to flush the foreign object out of your eye

2. The height of the baseboard installed on the working platform of the scaffold should not be any less than:
 - a. 125mm
 - b. 150mm
 - c. 175mm
 - d. 200mm

3. What is the correct storage method of the sack of cement?
 - a. Put it on a shelf and cover it with waterproof material
 - b. Put them on mud surface
 - c. Put them in open area
 - d. Pile them up

4. What is the requirement on sealing of the sides of mortar?
 - a. All sides should be sealed
 - b. 1 of the sides should not be sealed
 - c. 2 of the sides should not be sealed
 - d. 4 of the sides should not be sealed

5. What is the ideal amount of mortar left?
 - a. Over 3 mud buckets
 - b. None
 - c. Over 5 mud buckets
 - d. Over 1 mud bucket

6. What is requirement on the saturation level of the bedding sand?
 - a.Holes are seen at 5 locations or above
 - b.Holes are seen at 1 location
 - c.No holes shall be seen
 - d.Holes are seen at 3 locations or above

7. The deviation of angles shall not exceed:
 - a.5mm
 - b.Less than 5mm
 - c.10mm
 - d.15mm

8. Which of the following is a necessary preparation work before construction?
 - a.Clear the gravels
 - b.Allocate the stone materials appropriately in accordance with the drawing
 - c.Clear the tools
 - d.Keep the floor wet

9. Which of the following is not a standard of craftsmanship?
 - a.Checking tools
 - b.Straightened and even top plates
 - c.Refurbishment technique of stone materials
 - d.Mixing of bedding sand and moisture control

10. What does precaution include?
 - a.No clearance of tools
 - b.No inspection of chalk line
 - c.No inspection on the wall condition
 - d.Clearance of gravels and sand grout at work

11. What is the cause of pinholes in gap between stones?
 - a. Uneven surface of joint gap
 - b. Incompetent refurbishment of stone materials
 - c. Inadequate craftsmanship
 - d. Insufficient bedding grout

12. The deviation of angles shall not exceed:
 - a. 5mm
 - b. 20mm
 - c. 25mm
 - d. 30mm

13. If the length of connected straight gap does not exceed (three stones?), it means:
 - a. Pinholes are found in stones
 - b. The paving specification is accurate
 - c. Chalk line has not been inspected
 - d. The stone edge has not been dressed

14. Upon the completion of work, the surface of the stone should be:
 - a. The gap should not be clean
 - b. The surface of the stone should not be clean
 - c. Clean
 - d. Both the gap and the surface of the stones are not clean

15. A person should be serious at work and should uphold work ethics, including:
 - a. Accepting money and other advantages
 - b. Appropriation of other's property
 - c. Craving for personal interest and neglecting the damages dealt to others
 - d. Integrity that a person shall never accept illegal advantage and responsibility

16. Work ethic is a standard of evaluating work attitude. What is the advantage of complying with the standard?
- a. Leave without reason
 - b. Enhance efficiency, avoid making mistakes and promote credibility
 - c. More likely to make mistakes
 - d. Speed up the work progress so the duty can be over as soon as possible
17. Which of the following types of fire extinguishers is not suitable for use in fires caused by electrical failure?
- a. Carbon dioxide extinguisher
 - b. Powder extinguisher
 - c. Foam extinguisher
 - d. Bromochlorodifluoromethane extinguisher
18. Which of following is a safety measure for work?
- a. Placing of tools
 - b. Wearing a helmet
 - c. Ground dryness
 - d. Carrying identification documents
19. The "Ⓜ" symbol on a hand tool represents _____.
- a. A fire protection design
 - b. An earthing connection
 - c. An explosion-proof design
 - d. Double insulation
20. In which of the following situations is earthing arrangement not a must for portable electrical equipment?
- a. With an operating voltage lower than 220V
 - b. Used by registered and qualified professionals
 - c. With a double insulation structure
 - d. Used by electricians with license issued by the Electrical and Mechanical Services Department (EMSD)