



CONSTRUCTION
INDUSTRY COUNCIL
建造業議會

Plant and Equipment Operator (Tunneling) - Segment Erection Trade Test Mock Written Test Paper

此文件關於機械設備操作工（隧道）- 拱塊安裝工藝測試考題有需要索取此文件的中文版本，請致電 2100 9000 與香港建造業工藝測試中心聯絡。

Disclaimer

No part of this material may be reproduced or transmitted in any form or any means without the written permission of the CIC. Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions.

Enquiries

Enquiries on this Material may be made to the Hong Kong Construction Industry Trade Testing Centre at:

95, Yue Kwong Road
Aberdeen
Hong Kong

Tel: (852) 2100 9000
Fax: (852) 2100 9090
Email: enquiry@cic.hk
Website: www.cic.hk

1. On the vacuum erector, what does the sign S.W.L 10 ton mean ?
 - (a) load of moving object must not be greater than 10 ton
 - (b) if load is greater than 10 ton, machine can only be used when additional hydraulic jacks are installed
 - (c) working time of vacuum must be maintained within 10 mins
 - (d) hydraulic oil must be added every 10 mins

2. What is the common hand tools used for installing concrete segment ?
 - (a) chain block
 - (b) welding machine
 - (c) air gun
 - (d) coupler

3. Which one is the installation/connection method for concrete segment ?
 - (a) shear force
 - (b) spear bolts connection
 - (c) reinforcement bending
 - (d) reinforcement connection

4. What should you do when there is a power failure during vacuum erector operation ?
 - (a) secure segment on ground, turn on backup power immediately
 - (b) record time of power failure, to avoid punishment by supervisor
 - (c) no need to secure segment, inform electrician immediately
 - (d) arrange workers to erect temporary support below segment

5. Please choose the correct function of a vacuum erector
- (a) raising segment
 - (b) lifting & moving segment
 - (c) lifting locomotive
 - (d) to be used as temporary support
6. During segment installation, can TBM be operating at the same time ?
- (a) cannot, when operating together will increase wear on machine
 - (b) cannot, ring must be completed before continue excavation for annulus grouting
 - (c) can, because operation are not related to each other
 - (d) can, depends on skill of vacuum erector operator
7. During segment erection, hydraulic thrust ram must be extended to support segment, what is the main function of the thrust ram ?
- (a) to ensure enough space for segment erection
 - (b) to avoid personnel falling from height
 - (c) to increase the stability of vacuum erector
 - (d) to ensure segment erected is secure
8. Does operator has to follow the segment number during segment erection ?
- (a) Yes, to allow easy assessment of progress
 - (b) Yes, each segment has been numbered based on their relative position
 - (c) no, operator can decide themselves
 - (d) no, the segment number is for record purpose only

9. During lifting operation of segment, how should the segment be placed to avoid accident ?
- (a) increase the number of worker
 - (b) place lower than vacuum erector
 - (c) place segment on top of each other
 - (d) ensure the chosen placing location of segment will not cause overloading on machine
10. In which circumstances can vacuum erector be released safely ?
- (a) decide freely by operator
 - (b) operator to check to ensure segment connection is secured before releasing
 - (c) must complete grouting before releasing
 - (d) must inform safety officer before releasing
11. Before segment installation, operator should pay attention to which of the following ?
- (a) inspect segment to check for water leakage
 - (b) arrange enough manpower to install temporary support
 - (c) wrap segment in protective material to avoid damage
 - (d) check erection position of segment
12. How can operator safely install segment ?
- (a) use hydraulic thrust ram
 - (b) use strong adhesive
 - (c) use chain block
 - (d) pay attention to sound during installation

13. During segment lifting operation by vacuum erector, which of the following should pay attention to?
- (a) must finish install segment within time limit
 - (b) the sudden explosion of segment during lifting
 - (c) the stability of vacuum erector during lifting
 - (d) to minimize noise from vacuum erector during lifting
14. Before lifting and installation of segment, what should be prepared in advance ?
- (a) prepare aerial platform
 - (b) prepare adequate number of spear bolts
 - (c) increase vacuum suction pressure
 - (d) turn on alarm
15. Is the weight and shape of segment within one ring exactly ?
- (a) yes, they are
 - (b) no, different weight but same shape
 - (c) no, same weight but different shape
 - (d) no, different due to the design
16. What is the purpose of annulus grouting after segment installation ?
- (a) no purpose, routine work
 - (b) filling connection joint of segment
 - (c) to increase the sticking strength of segment on the tunnel
 - (d) to fill the annulus gap between segment and excavated tunnel
17. During segment installation, how can operator ensure a good quality ?
- (a) prior inspection of segment to check for damages and crack
 - (b) operator should check the concrete by hitting segment with hammer
 - (c) replace segment if there is a slight difference in colour
 - (d) none of the above

18. Can two operators operate two vacuum erector separately at the same time during segment installation ?
- (a) can, to increase progress
 - (b) can, depends on the number of operator
 - (c) can, because vacuum erector are located on both side and can be used at the same time
 - (d) cannot, because large amount of space is required for the erector
19. If cracks have been discovered at the bolt pocket, what should you do ?
- (a) repair with grout yourself and continue
 - (b) drill extra bolt pocket for replacement
 - (c) stop and inform supervisor
 - (d) use other bolt pocket for lifting
20. What safety precaution should be in place to protect other worker during segment erection ?
- (a) inform everyone to stay away from the area
 - (b) insolate erection area and lock the operators cabin
 - (c) if needed to work in erection area, prior agreement with operator is required
 - (d) during installation, must provide a walking access between the left and right side

21. Which of the following should pay attention to when installing segment ?
- (a) must ensure body parts of worker is in safe position before moving segment
 - (b) must spray concrete segment with water constantly for curing
 - (c) must have the supervision from safety officer
 - (d) none of the above
22. During segment erection, operation should pay attention to :
- (a) if worker has enough strength to do the job
 - (b) if there are enough workers
 - (c) if proper PPE has been used
 - (d) the correct hand signal by workers
23. During segment erection, why should operator pay attention to hand signal of the other worker?
- (a) for recording working time
 - (b) to speed up the progress
 - (c) to understand the number of segment for transportation
 - (d) to avoid accident
24. Operator must be appointed by the company, the reason is :
- (a) to ensure the quality of built ring
 - (b) to reduce installation time
 - (c) reduce wear on machine to prolong machine life
 - (d) ensure safe and competent operation

25. What should operator pay attention to during operation ?
- (a) water leakage on tunnel
 - (b) noise from machine parts
 - (c) if there are any workers inside operation area
 - (d) if nearby worker is smoking
26. After ring is built, how can operator ensure the safety of erector ?
- (a) remove vacuum erector from support beam
 - (b) remove key from control box
 - (c) remove battery from machine
 - (d) remove fuel completely to avoid fire
27. During segment installation, what warning sign should be in place near erection area?
- (a) beware of slippery floor
 - (b) wear ear protection
 - (c) do not enter erection area
 - (d) power stoppage time & date
28. During crane lifting operation, what does the hand signal mean in the picture ?

- (a) raising the hook
- (b) lowering the hook
- (c) lower the hook slowly
- (d) raise the hook slowly



29. During crane lifting operation, what does the hand signal mean in the picture ?

- (a) take a rest
- (b) stop immediately
- (c) crane is ready to drive
- (d) raising the job



30. During crane lifting operation, what does the hand signal mean in the picture ?

- (a) take a rest
- (b) stop immediately
- (c) drive slowly in a closer distance
- (d) ready to start

