



CONSTRUCTION  
INDUSTRY COUNCIL  
建造業議會

# Painter and Decorator (Surface Filling) Trade Test Mock Written Test Paper

此文件關於髹漆及裝飾工（批填漆灰）工藝測試考題有需要索取此文件的中文版本，請致電 2100 9000 與香港建造業工藝測試中心聯絡。

## **Disclaimer**

*No part of this material may be reproduced or transmitted in any form or any means without the written permission of the CIC. Whilst reasonable efforts have been made to ensure the accuracy of the information contained in this material, the CIC nevertheless would encourage readers to seek appropriate independent advice from their professional advisers where possible and readers should not treat or rely on this material as a substitute for such professional advice for taking any relevant actions.*

## **Enquiries**

Enquiries on this Material may be made to the Hong Kong Construction Industry Trade Testing Centre at:

95, Yue Kwong Road  
Aberdeen  
Hong Kong

Tel: (852) 2100 9000  
Fax: (852) 2100 9090  
Email: [enquiry@cic.hk](mailto:enquiry@cic.hk)  
Website: [www.cic.hk](http://www.cic.hk)

1. In accordance with the law, the worker entering the construction site must wear \_\_\_\_\_
  - a. A hard hat
  - b. A pair of cotton gloves
  - c. Rubber gloves
  - d. Safety belts
  
2. Which department does one apply for a license while establishing an inflammable dangerous goods
  - a. Fire Services Department
  - b. Labour Department
  - c. Hong Kong Police Force
  - d. Housing Department
  
3. If the following chemical labels is stated on the chemicals, what kind of property does it possess?
  - a. Toxic
  - b. Harmful
  - c. Inflammable
  - d. Explosive



4. If the following chemical labels is stated on the chemicals, what kind of property does it possess?
  - a. Toxic
  - b. Harmful
  - c. Inflammable
  - d. Explosive



5. Which of the following materials could shorten the drying time of double size filler with varnish mixture by hand at the highest rate ?
  - a. Double size
  - b. White limestone powder
  - c. Varnish
  - d. Gypsum powder
  
6. If one needs to paint on Tessera, which of the following materials is the most suitable to flatten its surface before painting?
  - a. Patching paste
  - b. Joint compound
  - c. White glue-double size filler
  - d. Tile filler
  
7. The main reason for commonly using white glue as adhesive in the mixture of white glue-double size filler for the newly plastered wall is that \_\_\_\_\_.
  - a. White glue is easy to access
  - b. White glue is easy to clean
  - c. The consistency of mixture is thicker than that of the one mixed with varnish
  - d. The mixture with white glue added would not cause saponification easily
  
8. The skimcoat (extra fine) putty for paint is the most suitable for applying on the surface of
  - a. Wood
  - b. PVC board
  - c. Stainless steel
  - d. Cement plastering
  
9. By mixing double size filler with varnish by hand, the function of varnish is
  - a. To increase the glossiness
  - b. To shorten the time for drying


- c. To use as a drying agent
- d. To act as an adhesive to strengthen the cohesion of the filler

10. What is the function of paper joint tapes on the joints of gypsum board?

- a. To increase the glossiness
- b. To increase the flexibility of the filler
- c. To shorten the time for fillers to dry
- d. To strengthen the crack resistance in the joints of the gypsum board

11. Which of the following signs represents concrete?

- a. A
- b. B
- c. C
- d. D



12. Double size that stored for too long will \_\_\_\_\_

- a. Rancid and grease
- b. Rancid and sweat
- c. Dry and vapourise
- d. Dry and soften

13. How many number of hours should be taken to use up the tile filler mixture after adding the water?

- a. 2-3 hours
- b. 7-8 hours
- c. 9-10 hours
- d. 11-12 hours

14. The joints between plaster board could be handled by

- a. Sticking newspaper to the plaster
- b. No sticking treatment
- c. Sticking paper towel to the plaster
- d. Sticking paper joint tape to the plaster

15. The main component of gypsum powder that used for filling joints is \_\_\_\_\_
- Calcium carbonate
  - Calcium sulphate
  - Calcium oxide
  - Iron(III) oxide
16. Which of the following primers could prevent the grease of solid wood depositing on its surface?
- Flat enamel prime
  - Asphalt primer
  - Aluminium primer
  - Antifouling paint
17. What kind of tools should be used for surface filling and patching up?
- Painting trowel
  - Steel Plate For Filling
  - Paint scraper
  - All of the above
18. The usual width of paint scraper bought from the market is \_\_\_\_\_.
- 1 inches
  - 2 inches
  - 3 inches
  - All of the above
19. Which of the following safety practices should a painter possess?
- Smoking is forbidden during work
  - Distant the flammable products from fire and take safety precaution
  - Take proper safety precaution to prevent accidents from happening
  - All of the above

20. In violating the section 9 of the Prevention of Bribery Ordinance, the maximum penalty is \_\_\_\_\_.

- a. Imprisonment for 10 years
- b. Imprisonment for 20 years
- c. A fine of \$10,000 and imprisonment for 1 year
- d. A fine of \$500,000 and imprisonment for 7 years

- End of Paper -